



IBM Power Systems Facts and Features:

Enterprise and Scale-out Systems with POWER8® Processor Technology



Table of contents	Page no.
Notes	3
Why Power Systems	4
IBM Power System S812LC, S822LC for Commercial Computing, S822LC for HPC, S822LC for Big Data and S821LC	5
IBM Power System S812L and S822L	6
IBM Power System S824L	7
IBM Power System S814 and S824	8
IBM Power System S812 and S822	9
IBM Power System E850C	10
IBM Power System E850	11
IBM Power System E870C	12
IBM Power System E870	13
IBM Power System E880C	14
IBM Power System E880	15
System S Class System Unit Details	16-19
Enterprise System, E850 System Unit and E870/E880 Node & Control Unit Details	19-20
Server I/O Drawers & Attachment	21-22
Physical Planning Characteristics	23
Warranty / Installation	24
Scale-out LC Server Systems Software Support	25
System S Class Systems Software Support	26-27
Enterprise Systems Software Support	28
Performance Notes & More Information	29

IBM® Power Systems™ servers and IBM BladeCenter® blade servers using IBM POWER7® and POWER7+® processors are described in a separate Facts and Features report dated July 2013 (POB03022-USEN-28).

IBM Power Systems servers and IBM BladeCenter® blade servers using IBM POWER6® and POWER6+™ processors are described in a separate Facts and Features report dated April 2010 (POB03004-USEN-14).

IBM Power Systems

These notes apply to the description tables for the pages which follow:

Y	Standard / Supported
Optional	Optionally Available / Supported
N/A or – n/a	Not Available / Supported or Not Applicable
SOD	Statement of General Direction announced
SLES	SUSE Linux Enterprise Server
RHEL	Red Hat Enterprise Linux
A	CoD capabilities include: Capacity Upgrade on Demand option – permanent processor or memory activation, Elastic Capacity on Demand – temporary processor or memory activation by the day, Utility Capacity on Demand – temporary processor activation by the minute, and Trial Capacity on Demand.
B	Withdraw from marketing date generally true world wide, but there may be specific countries exceptions
a	For IBM Manufacturing processes, one x8 PCIe slots must contain an Ethernet LAN. The adapter is available for client use.
b	Use of expanded function storage backplane uses one PCIe slot in 2U servers and optionally uses a PCIe slot in 4U servers
c	Backplane provides dual high performance SAS controllers with 1.8 GB write cache expanded up to 7.2 GB with compression plus Easy Tier function plus two SAS ports for running an EXP24S drawer. 4-core S814 or 1-core S812 do not support the attachment of an EXP24S to these ports
d	Full benchmark results are located at ibm.com/systems/power/hardware/reports/system_perf.html
e	Option is supported on IBM i only through VIOS.
f	For simplicity in calculating maximum and consistently describing the max across the Scale-out Servers, the 12-bay backplane is assumed. A higher max with the expanded function backplane is possible.
g	USB-2 ports have limited client usage compared to USB-3 ports. Clients can use a USB-2 port to communicate with a UPS
h	4-core Power S814 max capacity disk drive supported in system unit is 600 GB.
j	Not available in PowerKVM environment
k	Maximum memory for 4.1GHz S822 and S822L is 512 GB unless water cooling is used.
m	Except one predefined configuration (8-Core #EHJW) has only 32 GB
n	The 4.1 GHz S822 requires water cooling to attain full rPerf values. With air cooling SMT8 is not supported reducing the rPerf values about 8 percent. Also the memory maximum is 50 percent lower.
o	Values for 64-, 96- and 128-core servers measured as multiples of 32-core partitions. Values for 96-, 144- and 192-core servers measured as multiples of 48-core partitions. Values for 80-, 120-, and 160-core servers measured as multiples of 40-core partitions.
p	When no GPU installed
q	Slot total shown are all available PCIe slots for client use. PCIe slots in the system unit used to attach a PCIe Gen3 I/O drawer are excluded from total. Note one x8 PCIe slots must contain an Ethernet LAN available for client use
r	Can convert E850C/E870C/E880C Elastic CoD processor days to IBM SoftLayer resources. Can convert E870C/E880C mobile processor activations to IBM SoftLayer resources
s	On Power S822, max size of 2-cores per IBM i partition prior to firmware 860, max of 4-cores with FW 860. Multiple IBM i partitions supported. The software tier is on P10.
t	HMC Applications as a Service is a technology preview as of October 2016. It is a Statement of Direction. All IBM SODs are subject to change without notice.

For additional connectivity information, please reference the IBM Sales Manual for more information on I/O features and adapters.

Why Power Systems?

Powerful forces—mobile, cloud and big data & analytics—are redefining how business gets done. Leaders are leveraging these forces to deepen relationships with customers and partners, drive new efficiencies and expand business models. IBM is the right partner to help you:

Leverage systems that optimize big data and analytics performance.

Power Systems are designed for big data—from operational to computational to business and cognitive Watson solutions—are optimized for performance and can scale to support demanding and growing workloads. Capitalize on the currency of data by finding business insights faster and more efficiently. And gain the elasticity you need to handle the varying analytics initiatives your business requires.

Realize the true potential of enterprise cloud.

Power Systems will help you deliver on the promise of cloud and take advantage of superior cloud economics. With higher utilization and performance capabilities and the ability to scale out and up, you can reap the benefits of improved economics associated with fewer scale-out systems. Leveraging the robust security built into the foundation of Power Systems, you gain the confidence you need to move more workloads to the cloud, capitalize on greater efficiencies and do more.

Revolutionize the way IT is created and consumed.

POWER architecture is at the heart of the OpenPOWER Foundation, a community that's taking advantage of an open technology platform to help organizations create new opportunities and design next-generation applications to drive business success. The first to adopt open server technology, Power Systems help you more quickly and easily deliver a broader set of services and incorporate new technologies using the same technology footprint

Follow us @IBMpowersystems

Learn more at www.ibm.com/power

Power S812LC, Power S822LC for Commercial Computing, Power S822LC for High Performance Computing, Power S822LC for Big Data, and S821LC

Product Line	IBM Power S812LC	IBM Power S822LC for Commercial Computing	IBM Power S822LC for HPC	IBM Power S822LC for Big Data	S821LC
Machine type	8348-12C	8335-GCA	8335-GTB	8001-22C	8001-12C
System packaging	19" rack drawer (2U)	19" rack drawer (2U)	19" rack drawer (2U)	19" rack drawer (2U)	19" rack drawer (1U)
Microprocessor type	64-bit POWER8	64-bit POWER8	64-bit POWER8 with NVLink	64-bit POWER8	64-bit POWER8
# of processor sockets per server	1	2	2	1-2	1-2
Processor options GHz (cores/socket) # of cores	3.32 GHz (8) 8 2.92 GHz (10) 10	3.32 GHz (8) 16 2.92 GHz (10) 20	3.32 GHz (8) 16 2.92 GHz (10) 20	3.32 GHz (8) 8 or 16 2.92 GHz (10) 10 or 20 2.89 GHz (11) 11 or 22	2.32 GHz (8) 8 or 16 2.09 GHz (10) 10 or 20
EnergyScale	N/A	N/A	N/A	N/A	N/A
Level 2 (L2) cache per core	512 KB	512 KB	512 KB	512 KB	512 KB
Level 3 (L3) cache per core	8 MB	8 MB	8 MB	8 MB	8 MB
Level 4 (L4) cache per socket	Up to 64 MB	Up to 64 MB	Up to 64 MB	Up to 64 MB	Up to 64 MB
System memory (minimum - maximum)	128 GB ^m – 1024 GB	32 GB – 1024 GB	128 GB – 1024 GB	32 GB – 512 GB	32 GB – 512 GB
Memory Type	1333MHz DDR3	1333MHz DDR3	1600MHz DDR4	1600MHz DDR4	1600MHz DDR4
Acceleration	N/A	Up to 2x NVIDIA K80 GPUs	2 or 4 NVIDIA P100 GPUs with NVLink GPU-GPU and GPU-CPU	Up to 2x NVIDIA K80 GPUs	Up to 1x NVIDIA K80 GPU
Water Cooling	N/A	N/A	Y	N/A	N/A
Reliability, availability, serviceability					
Chipkill memory	Y	Y	Y	Y	
Baseboard Management Controller	Y	Y	Y	Y	Y
Hot-swappable disk/SSD bays	Y(front only)	N	N	Y (HDD/SSD only)	Y (HDD/SSD only)
Processor Instruction Retry	Y	Y	Y	Y	Y
Redundant hot-plug power	Y	N	Y ^p	Y	Y
Redundant hot-plug cooling	Redundant but not hot-plug	Y	Y	N	Redundant but not hot-plug
Capacity and expandability					
Capacity on Demand (CoD)	N/A	N/A	N/A	N/A	N/A
PowerVM PowerLinux Edition	N/A	N/A	N/A	N/A	N/A
PowerKVM 3.1 Edition	Optional	Optional			
PowerVM Standard Edition	N/A	N/A	N/A	N/A	N/A
PowerVM Enterprise Edition	N/A	N/A	N/A	N/A	N/A
Max logical partitions/micro-partitions	N/A	N/A	N/A	N/A	N/A
System unit PCIe Gen3 slots ^a	3 PCIe x8 1 PCIe x16	2 PCIe x8 3 PCIe x16	2 PCIe x8 3 PCIe x16		
Max PCIe Gen3 I/O Drawer	N/A	N/A	N/A	N/A	N/A
System unit disk/SSD bays	2 with mezz controller 12 more with PCIe adapter	2 SFF-4	2 SFF-4	8x LFF/SFF SATA from Planar 12x LFF/SFF SATA/SAS/NVMe with PCIe storage controllers	4x LFF/SFF SATA from Planar 4x LFF/SFF SATA/SAS/NVMe with PCIe Storage controllers
Slimline DVD bay	N	N	N	N	N
Maximum TB storage in system unit	84.0TB (with 14x6TB)	2.0 TB (with 2x 1TB disks)	4.0TB (with 2x 1TB disks)	96.0TB (with 12x 8TB)	32.0TB (with 4x 8TB)
Maximum EXP24S storage drawers	N/A	N/A	N/A	N/A	N/A

Power S812L and S822L

Product Line	IBM Power S812L	IBM Power S822L
Machine type	8247-21L	8247-22L
System packaging	19" rack drawer (2U)	19" rack drawer (2U)
Microprocessor type	64-bit POWER8	64-bit POWER8
# of processor sockets per server	1	2
Processor options GHz (cores/socket) # of cores	3.42 GHz (10) 10 3.02 GHz (12) 12	3.42 GHz (10) 20 3.02 GHz (12) 24 4.15 GHz (8) 16
EnergyScale	Y	Y
Level 2 (L2) cache per core	512 KB	512 KB
Level 3 (L3) cache per core	8 MB	8 MB
Level 4 (L4) cache per socket	Up to 128 MB	Up to 128 MB
System memory (minimum – maximum) (1600 MHz DDR4)	16 GB – 512 GB	32 GB -1024 GB ^k
Active Memory Expansion	N/A	N/A
Reliability, availability, serviceability		
Chipkill memory	Y	Y
Service processor	Y	Y
Hot-swappable disks/ SSD	Y	Y
Dynamic Processor Deallocation	Y ^j	Y ^j
Processor Instruction Retry	Y ^j	Y ^j
Alternate Processor Recovery	Y ^j	Y ^j
Hot-plug concurrent maintenance PCIe slots	Y ^j	Y ^j
Redundant hot-plug power	Y	Y
Redundant hot-plug cooling	Y	Y
Node Add, Node Repair, Memory Upgrade	N/A	N/A
Dual VIOS	Optional ^j	Optional ^j
Capacity and expandability		
Capacity on Demand (CoD)	N/A	N/A
PowerVM PowerLinux Edition	Optional	Optional
PowerKVM Edition	Optional	N/A
PowerVM Standard Edition	N/A	Optional
PowerVM Enterprise Edition	N/A	N/A
Max logical partitions/micro-partitions	240	480
System unit PCIe Gen3 low profile slots ^a	4 PCIe x8 2 PCIe x16	5 PCIe x8 4 PCIe x16
Max PCIe Gen3 I/O Drawer	½	1
Max PCIe Gen3 slots: system unit + PCIe I/O drawers ^q	10 (4 in system unit + 6 in I/O drawer) ^q	17 (5 in system unit + 12 in I/O drawer) ^q
System unit disk/SSD bays with standard or split backplane	12 SFF-3 or 6+6 SFF-3	12 SFF-3 or 6+6 SFF-3
System unit disk/SSD bays with expanded function backplane and dual IOA with 7.2GB write cache ^{b, c}	8 SFF-3 plus optional EXP24S attachment for an additional 24 SFF-2 bays	8 SFF-3 plus 6 1.8-inch SSD bays plus optional EXP24S attachment for an additional 24 SFF-2 bays
Slimline DVD bay	1	1
Maximum TB storage in system unit	21.6 TB (with 12x 1.8 TB disks)	21.6 TB (with 12x 1.8 TB disks)
Maximum EXP24SX/EXP24S/EXP12SX storage enclosures	28	28
Maximum in EXP24SX/EXP24S	672 drives 1209 TB w/ 1.8 TB disk	672 drives 1209 TB w/ 1.8 TB disk
Maximum in EXP12SX	336 drives 2593 TB w/ 7.72 TB disk	336 drives 2593 TB w/ 7.72 TB disk
Performance ^d		
AIX rPerf GHz (cores/socket): perf (# cores)	N/A	N/A
IBM i CPW GHz (cores/socket): perf (# cores)	N/A	N/A

IBM Power Systems
Power S824L

Product Line	IBM Power S824L	IBM Power S824L ^P
Machine type	8247-42L	8247-42L
System packaging	19" rack drawer (4U)	19" rack drawer (4U)
Microprocessor type	64-bit POWER8	64-bit POWER8
# of processor sockets per server	2	2
Processor options	3.42 GHz (10) 20	4.15 GHz (8) 8 or 16
GHz (cores/socket) # of cores	3.02 GHz (12) 24	3.52 GHz (12) 24
EnergyScale	Y	Y
Level 2 (L2) cache per core	512 KB	512 KB
Level 3 (L3) cache per core	8 MB	8 MB
Level 4 (L4) cache per socket	Up to 128 MB	Up to 128 MB
System memory (minimum - maximum) (1600 MHz DDR4)	32 GB –2048 GB	32 GB –2048 GB
Active Memory Expansion	N/A	N/A
Reliability, availability, serviceability		
Chipkill memory	Y	Y
Service processor	Y	Y
Hot-swappable disks	Y	Y
Dynamic Processor Deallocation	Y	Y
Processor Instruction Retry	Y	Y
Alternate Processor Recovery	N/A	N/A
Hot-plug concurrent maintenance PCIe slots	N/A	N/A
Redundant hot-plug power	Y	Y
Redundant hot-plug cooling	Y	Y
Node Add, Node Repair, Memory Upgrade	N/A	N/A
Dual VIOS	Optional	Optional
Capacity and expandability		
Capacity on Demand (CoD)	N/A	N/A
Active Memory Expansion	N/A	N/A
PowerVM PowerLinux Edition	N/A	Y
PowerKVM Edition	N/A	Optional
PowerVM Standard Edition	N/A	N/A
PowerVM Enterprise Edition	N/A	N/A
Max logical partitions/micro partitions	N/A	480
System unit PCIe Gen3 full high slots ^a	7 PCIe x8 4 PCIe x16	7 PCIe x8 4 PCIe x16
Max PCIe Gen3 I/O Drawers	N/A	2
Max PCIe Gen3 slots: system unit + PCIe I/O drawers	7 in system unit	31 (7 in system unit + 24 in I/O drawer) ^q
System unit disk bays with standard backplane	12 SFF-3	12 SFF-3
System unit disk/SSD bays with expanded function backplane and dual IOA with 7.2GB write cache ^{b, c}	N/A	18 SFF-3 plus 8 1.8-inch SSD bays plus optional EXP24S attachment for an additional 24 SFF-2 bays
Slimline DVD bay	1	1
Maximum TB storage in system unit	14.4 TB (with 12 ^f x 1.2 TB disks)	21.6 TB (with 12 ^f x 1.8 TB disks)
Maximum EXP24SX/EXP24S/EXP12SX storage enclosures	N/A	28
Maximum in EXP24SX/EXP24S	N/A	672 drives 1209 TB w/ 1.8 TB disk
Maximum in EXP12SX	N/A	336 drives 2593 TB w/ 7.72 TB disk
Performance^d		
AIX rPerf	N/A	N/A
GHz (cores/socket): perf (# cores)	N/A	N/A
IBM i CPW	N/A	N/A
GHz (cores/socket): perf (# cores)	N/A	N/A

Power S814 and Power S824

Product Line	IBM Power S814	IBM Power S824
Machine type	8286-41A	8286-42A
System packaging	19" rack drawer (4U)	19" rack drawer (4U)
Microprocessor type	64-bit POWER8	64-bit POWER8
# of processor sockets per server	1	2
Processor options GHz (cores/socket) # of cores	3.02 GHz (4) 4 3.02 GHz (6) 6 3.72 GHz (8) 8	3.89 GHz (6) 6 or 12 4.15 GHz (8) 8 or 16 3.52 GHz (12) 24
EnergyScale	Y	Y
Level 2 (L2) cache per core	512 KB	512 KB
Level 3 (L3) cache per core	8 MB	8 MB
Level 4 (L4) cache per socket	Up to 128 MB	Up to 128 MB
System memory (minimum - maximum) (1600 MHz DDR4)	4-core: 16 GB – 64 GB 6/8-core: 16 GB – 1024 GB	32 GB – 1 TB (1 DCM) 32 GB – 2 TB (2 DCM)
Active Memory Expansion	Optional	Optional
Reliability, availability, serviceability		
Chipkill memory	Y	Y
Service processor	Y	Y
Hot-swappable disks	Y	Y
Dynamic Processor Deallocation	Y	Y
Processor Instruction Retry	Y	Y
Alternate Processor Recovery	Y	Y
Hot-plug concurrent maintenance PCIe slots	Y	Y
Redundant hot-plug power	Y	Y
Redundant hot-plug cooling	Y	Y
Node Add, Node Repair, Memory Upgrade	N/A	N/A
Dual VIOS	Optional	Optional
Capacity and expandability		
Capacity on Demand (CoD)	N/A	N/A
PowerVM PowerLinux Edition	N/A	N/A
PowerKVM Edition	N/A	N/A
PowerVM Standard Edition	Optional	Optional
PowerVM Enterprise Edition	Optional	Optional
Max logical partitions/micro-partitions	160	480
System unit PCIe Gen3 full high slots ^a	5 PCIe x8 2 PCIe x16	7 PCIe x8 4 PCIe x16
Max PCIe Gen3 I/O Drawer	1	2
Max PCIe Gen3 slots: system unit + PCIe I/O drawers ^g	17 (5 in system unit + 12 in I/O drawer) ^g	31 (7 in system unit + 24 in I/O drawer) ^g
System unit disk/SSD bays with standard or split backplane	4-core : 10 SFF-3 or 5+5 SFF-3 6/8-core : 12 SFF-3 or 6+6 SFF-3	12 SFF-3 or 6+6 SFF-3
System unit disk/SSD bays with expanded function backplane and dual IOA with 7.2GB write cache ^{b,c}	4-core: 10 SFF (no EXP24S) 6/8-core:18 SFF-3 plus optional EXP24S attachment for an additional 24 SFF-2 bays	18 SFF-3 plus 8 1.8-inch SSD bays plus optional EXP24S attachment for an additional 24 SFF-2 bays
Slimline DVD bay	1	1
Maximum TB storage in system unit	4-core : 6.0TB (with 10x600GB) 6/8-core 32.4TB (with 18x 1.8TB disk)	35.4 TB (with 18x 1.8 TB disks plus 8x 387 GB SSD)
Maximum EXP24SX/EXP24S/ EXP12SX storage enclosures ^{f h}	4-core: 0 6/8-core: 28	28
Maximum in EXP24SX/EXP24S ^{f h}	672 drives for 6/8-core 1209 TB w/ 1.8 TB disk	672 drives 1209 TB w/ 1.8 TB disk
Maximum in EXP12SX ^{f h}	336 drives for 6/8-core 2593 TB w/ 7.72 TB disk	336 drives 2593 TB w/ 7.72 TB disk
Performance ^d		
AIX rPerf GHz (cores/socket): perf (# cores)	3.02 GHz (4) : 66.9 3.02 GHz (6) : 97.5 3.72 GHz (8) : 143.9	3.89 GHz (6) : 120.8 4.15 GHz (8) : 166 3.89 GHz (12) : 235.6 4.15 GHz (16) : 323.6 3.52 GHz (24) : 421.9
IBM i CPW ^s GHz (cores/socket): perf (# cores)	3.02 GHz (4) : 39,500 3.02 GHz (6) : 59,500 3.72 GHz (8) : 85,500	3.89 GHz (6) : 72,000 4.15 GHz (8) : 94,500 3.89 GHz (12) : 130,000 4.15 GHz (16) : 173,500 3.52 GHz (24) : 230,500

Power S812 and S822

Product Line	IBM Power S812	IBM Power S822
Machine type	8284-21A	8284-22A
System packaging	19" rack drawer (4U)	19" rack drawer (2U)
Microprocessor type	64-bit POWER8	64-bit POWER8
# of processor sockets per server	1	2
Processor options GHz (cores/socket) # of cores	3.02 GHz (1) 1 3.02 GHz (4) 4	3.02 GHz (4) 4 3.89 GHz (6) 6 or 12 3.42 GHz (10) 10 or 20 4.15 GHz (8) 8 or 16
EnergyScale	Y	Y
Level 2 (L2) cache per core	512 KB	512 KB
Level 3 (L3) cache per core	8 MB	8 MB
Level 4 (L4) cache per socket	Up to 128 MB	Up to 128 MB
System memory (minimum - maximum) (1600 MHz DDR4)	1-core: 16 GB – 64 GB 4-core: 16 GB – 128 GB	32 GB – 512 GB (1 DCM) 32 GB – 1024 GB (2 DCM)
Active Memory Expansion		Optional
Reliability, availability, serviceability		
Chipkill memory	Y	Y
Service processor	Y	Y
Hot-swappable disks	Y	Y
Dynamic Processor Deallocation	Y (4-core)	Y
Processor Instruction Retry	Y (4-core)	Y
Alternate Processor Recovery	Y (4-core)	Y
Hot-plug concurrent maintenance PCIe slots	Y	Y
Redundant hot-plug power	Y	Y
Redundant hot-plug cooling	Y	Y
Node Add, Node Repair, Memory Upgrade	N/A	N/A
Dual VIOS	N/A	Optional
Capacity and expandability		
Capacity on Demand (CoD)	N/A	N/A
PowerVM PowerLinux Edition	N/A	N/A
PowerKVM Edition	N/A	N/A
PowerVM Standard Edition	N/A	Optional
PowerVM Enterprise Edition	N/A	Optional
Max logical partitions/micro-partitions	1	400
System unit PCIe Gen3 full high slots ^a	4 PCIe x8 2 PCIe x16	5 PCIe x8 4 PCIe x16
Max PCIe Gen3 I/O Drawer	0	1
Max PCIe Gen3 slots: system unit + PCIe I/O drawers ^q	6	17 (5 in system unit + 12 in I/O drawer) ^q
System unit disk/SSD bays with standard or split backplane	1-core: 8 SFF-3 or 4+4 SFF-3 4-core: 12 SFF-3 or 6+6 SFF-3	12 SFF-3 or 6+6 SFF-3
System unit disk/SSD bays with expanded function backplane and dual IOA with 7.2GB write cache ^{b, c}	1-core: 8 SFF-3 4-core: 8SFF-3 plus optional EXP24SXor EXP12SX attachment for additional bays	8 SFF-3 plus 6 1.8-inch SSD bays plus optional EXP24S attachment for an additional 24 SFF-2 bays
Slimline DVD bay	1	1
Maximum TB storage in system unit	1-core: 4.5TB (with 8x571GB HDD) 4-core: 22TB (with 12x 1.9TB SSD)	22 TB (with 12x 1.9 TB SSD)
Maximum EXP24SX/EXP24S/ EXP12SX storage enclosures ^{f h}	1-core: 0 4-core: 3	28
Maximum in EXP24SX/EXP24S ^{f h}	72 drives for 4-core 129 TB w/ 1.8 TB disk	672 drives 1209 TB w/ 1.8 TB disk
Maximum in EXP12SX ^{f h}	36 drives for 4-core 277 TB w/ 7.72 TB disk	336 drives 2593TB w/ 7.72 TB disk
Performance ^d		
AIX rPerf GHz (cores/socket): perf (# cores)	3.02 GHz (4) 66.9	3.02 GHz (4): 66.9 (4) 3.42 GHz (10): 177.8 (10); 346.7 (20) 3.89 GHz (6): 120.8 (6), 235.6 (12) 4.15 GHz (8) ^r : 166.0 (8); 323.6 (16)
IBM i CPW ^s GHz (cores/socket): perf (# cores)	3.02 GHz (1): 9,880	3.42 GHz (10): 44,800 per 4core LPAR 3.89 GHz (6): 47,700 per 4core LPAR 4.15 GHz (8): 52,700 per 4core LPAR

IBM Power Systems
Power E850C

Product Line		IBM Power E850C			
Machine type	8408-44E				
System packaging	19" rack drawer (4U)				
Microprocessor type	64-bit POWER8				
# of processor sockets per server	4				
Processor options	4.22 GHz (8)	32 max	16	8	
GHz (cores/socket) max # of cores min # of cores min # of activations	3.95 GHz (10)	40 max	20	10	
	3.65 GHz (12)	48 max	24	12	
Energy scale	Yes				
Level 2 (L2) cache per core	512 KB				
Level 3 (L3) cache per core	8 MB				
Level 4 (L4) cache per socket	Up to 128 MB				
System memory: min / max / (min % active)	128 GB / 4 TB / (50%)				
1600 MHz DDR4					
Active Memory Expansion	Optional				
Reliability, availability, serviceability					
Chipkill memory	Yes				
Service processor	Yes				
Hot-swappable disks	Yes				
Phase redundant, integrated sparing voltage regulator modules for processors, memory and I/O	Yes				
Hot-swappable disks	Yes				
Dynamic Processor Deallocation	Yes				
Alternate Processor Recovery	Yes				
Hot plug PCIe slots	Yes				
Active Memory Mirroring	Optional				
Redundant hot-plug power	Yes				
Redundant fans for SAS controllers and drive bays	Yes				
Redundant, hot swappable fans for processor, memory and PCIe slots	Yes				
Dual VIOS	Optional				
Cloud Mgmt and Deployment					
IBM Cloud PowerVC Manager	Included (separately priced)				
HMC Apps as a Server [†]	No charge when available				
Cloud Starter Pack	6 months access				
Convert Power server resources to cloud [†]	Yes				
IBM API Connect and WebSphere Connect	Included				
Open source cloud automation and configuration tooling for AIX	Included				
Power-to-Cloud Rewards	5,000 points				
Capacity and expandability					
Capacity on Demand (CoD)	Yes				
Power Enterprise Pools	N/A				
Power Integrated facility for Linux	Optional				
PowerVM Enterprise Edition	Standard				
Max logical partitions/micropartitions	960 (20 per core)				
System unit PCIe Gen3 full high slots ^a	3 PCIe x8 plus 4-8 PCIe x16 (two x16 slots per installed processor module)				
Max PCIe Gen3 I/O Drawers	4				
Max PCIe Gen3 slots	51				
Slimline DVD bay	1				
Maximum TB storage in system unit	17.5 TB 8 x 1.8TB disks plus 4 x 1.8-inch 775 GB SSD				
Maximum EXP24S/EXP24SX/EXP12SX storage enclosures	64				
Max in EXP12SX	768 drives	5929 TB with 7.72 TB disk			
Max in EXP24S/EXP24SX	1536 drives	2764 TB with 1.8 GB disk			
Performance					
AIX rPerf	3.65 GHz (12): 221* (12), 440.7 (24), 640.0 (36), 859.3(48)				
GHz (cores/socket): perf (# cores) (*est)	3.95 GHz (10): 197* (10), 393.1 (20), 579.8 (30), 766.5(40)				
	4.22 GHz (8): 168* (8), 334.7 (16), 493.7 (24), 652.7(32)				

Power E850 (withdrawal from marketing announced Feb 2017, effective 17 July^B see E850C)

Product Line	IBM Power E850			
Machine type	8408-E8E			
System packaging	19" rack drawer (4U)			
Microprocessor type	64-bit POWER8			
# of processor sockets per server	4			
Processor options	3.7 GHz (8)	32	16	16
GHz (cores/socket) max # of cores min # of cores min # of activations	3.35 GHz (10)	40	20	20
	3.3 GHz (12)	48	24	24
Energy scale	Yes			
Level 2 (L2) cache per core	512 KB			
Level 3 (L3) cache per core	8 MB			
Level 4 (L4) cache per socket	Up to 128 MB			
System memory: min / max / (min % active) 1600 MHz DDR3 or DDR4	128 GB / 4 TB / (50%)			
Active Memory Expansion	Optional			
Reliability, availability, serviceability				
Chipkill memory	Yes			
Service processor	Yes			
Hot-swappable disks	Yes			
Phase redundant, integrated sparing voltage regulator modules for processors, memory and I/O	Yes			
Hot-swappable disks	Yes			
Dynamic Processor Deallocation	Yes			
Alternate Processor Recovery	Yes			
Hot plug PCIe slots	Yes			
Active Memory Mirroring	Optional			
Redundant hot-plug power	Yes			
Redundant fans for SAS controllers and drive bays	Yes			
Redundant, hot swappable fans for processor, memory and PCIe slots	Yes			
Dual VIOS	Optional			
Capacity and expandability				
Capacity on Demand (CoD)	Yes			
Power Enterprise Pools	N/A			
Power Integrated facility for Linux	Optional			
PowerVM	Optional			
Max logical partitions/micropartitions	960 (20 per core)			
System unit PCIe Gen3 full high slots ^a	3 PCIe x8 plus 4-8 PCIe x16 (2 x16 slots per installed processor module)			
Max PCIe Gen3 I/O Drawers	4			
Max PCIe Gen3 slots	51			
Slimline DVD bay	1			
Maximum TB storage in system unit	17.5 TB 8 x 1.8 TB disks plus 4 x 1.8" 775 GB SSD			
Maximum EXP24S/EXP24SX/EXP12SX storage enclosures	64			
Max in EXP12SX	768 drives 5928 TB with 7.72 TB drives			
Max in EXP24SX	1536 drives 2764 TB with 1.8 GB disk			
Performance				
AIX rPerf	3.02 GHz (12): 383.0(24), 565.0(36), 746.9(48)			
GHz (cores/socket): perf (# cores)	3.35 GHz (10): 347.8(20), 513.0(30), 678.3(40)			
	3.72 GHz (8): 304.5(16), 449.2(24), 593.8(32)			

IBM Power Systems
Power E870C

Product Line	IBM Power E870C (1 node)	IBM Power E870C (2 node)
Machine type	9080-MME	9080-MME
System packaging	19" rack drawer (7U) One 5U system node & one 2U system control unit	19" rack drawer (12U) Two 5U system nodes & one 2U system control unit
Microprocessor type	64-bit POWER8	64-bit POWER8
# of processor sockets per server	4	8 (4 per system node)
Processor options GHz (cores/socket) # of cores	4.02 GHz (8) 32	4.02 GHz (8) 64
Minimum number of core activations	8	8
Energy Scale	Y	Y
Level 2 (L2) cache per core	512 KB	512 KB
Level 3 (L3) cache per core	8 MB	8 MB
Level 4 (L4) cache per socket	Up to 128 MB	Up to 128 MB
System memory: min / max / (min % active) 1600 MHz DDR3 or DDR4	256 GB / 8 TB / (50%)	512 GB / 16 TB / (50%)
Active Memory Expansion	Optional	Optional
Reliability, availability, serviceability		
Chipkill memory	Y	Y
Service processor and clock	Redundant with failover	Redundant with failover
Hot-swappable disks	N/A	N/A
Dynamic Processor Deallocation	Y	Y
Processor Instruction Retry	Y	Y
Alternate Processor Recovery	Y	Y
Hot-plug PCIe slots	Y	Y
Blind-swap PCIe slots in system unit	Y	Y
Active Memory Mirroring	Y	Y
Redundant hot-plug power	Y	Y
Redundant hot-plug cooling	Y	Y
Dual VIOS	Optional	Optional
Cloud Mgmt and Deployment		
IBM Cloud PowerVC Manager	Included (separately priced)	Included (separately priced)
HMC Apps as a Server ^t	No charge when available	No charge when available
Cloud Starter Pack	12 months access	12 months access
Convert Power server resources to cloud ^r	Yes	Yes
IBM API Connect and WebSphere Connect	Included	Included
Open source cloud automation and configuration tooling for AIX	Included	Included
Power-to-Cloud Rewards	10,000 points	10,000 points
Capacity and expandability		
Capacity on Demand (CoD) functions	Y ^A	Y ^A
Power Enterprise Processor Pools	Optional	Optional
Power Integrated Facility for Linux	Optional	Optional
PowerVM Enterprise Edition	Standard	Standard
Max logical partitions/micro-partitions	640 (20 per core max)	1000
Max system node PCIe Gen3 x16 slots	8	16 (8 per node)
Max PCIe Gen3 I/O Drawers	4	8 (4 per node)
Max PCIe Gen3 slots: (all in PCIe Gen3 I/O drawers)	48 ^k	96 ^k
System Control Unit: media bay	1 optional DVD	1 optional DVD
Max disk storage in system node	N/A	N/A
Maximum EXP24S/EXP24SX/EXP12SX storage enclosures	64	128
Maximum in EXP12SX	768 drives 5929 TB w/ 7.72TB disk	1536 drives 11858 TB w/ 7.72TB disk
Maximum in EXP24SX/EXP24S	1536 drives 2764 TB w/ 1.8TB disk	3072 drives 5529 TB w/ 1.8TB disk
Performance*		
AIX rPerf GHz (cores/socket): perf (# cores)	4.02 GHz (8): 674.5(32),	4.02 GHz (8): 1,349.0(64) ^o
IBM i CPW GHz (cores/socket): perf (# cores)	4.02 GHz (8): 359,000(32),	4.02 GHz (8): 711,000(64) ^o

Power E870 (withdrawal from marketing announced Feb 2017, effective 17 July^B see E870C)

Product Line	IBM Power E870 (1 node)	IBM Power E870 (2 node)
Machine type	9119-MME	9119-MME
System packaging	19" rack drawer (7U) One 5U system node & one 2U system control unit	19" rack drawer (12U) Two 5U system nodes & one 2U system control unit
Microprocessor type	64-bit POWER8	64-bit POWER8
# of processor sockets per server	4	8 (4 per system node)
Processor options	4.02 GHz (8) 32 4.19 GHz (10) 40	4.02 GHz (8) 64 4.19 GHz (10) 80
Minimum number of core activations	8	8
Energy Scale	Y	Y
Level 2 (L2) cache per core	512 KB	512 KB
Level 3 (L3) cache per core	8 MB	8 MB
Level 4 (L4) cache per socket	Up to 128 MB	Up to 128 MB
System memory: min / max / (min % active) 1600 MHz DDR3	256 GB / 8 TB / (50%)	512 GB / 16 TB / (50%)
Active Memory Expansion	Optional	Optional
Reliability, availability, serviceability		
Chipkill memory	Y	Y
Service processor and clock	Redundant with failover	Redundant with failover
Hot-swappable disks	N/A	N/A
Dynamic Processor Deallocation	Y	Y
Processor Instruction Retry	Y	Y
Alternate Processor Recovery	Y	Y
Hot-plug PCIe slots	Y	Y
Blind-swap PCIe slots in system unit	Y	Y
Active Memory Mirroring	Y	Y
Redundant hot-plug power	Y	Y
Redundant hot-plug cooling	Y	Y
Dual VIOS	Optional	Optional
Capacity and expandability		
Capacity on Demand (CoD) functions	Y ^A	Y ^A
Power Enterprise Processor Pools	Optional	Optional
Power Integrated Facility for Linux	Optional	Optional
PowerVM Enterprise Edition	Standard	Standard
Max logical partitions/micro-partitions	800 (20 per core max)	1000
Max system node PCIe Gen3 x16 slots	8	16 (8 per node)
Max PCIe Gen3 I/O Drawers	4	8 (4 per node)
Max PCIe Gen3 slots: (all in PCIe Gen3 I/O drawers)	48 ^k	96 ^k
System Control Unit: media bay	1 optional DVD	1 optional DVD
Max disk storage in system node	N/A	N/A
Maximum EXP24S/EXP24SX/EXP12SX storage enclosures	64	128
Maximum in EXP12SX	768 drives 5929 TB w/ 7.72 TB disk	1536 drives 11858 TB w/ 7.72 TB disk
Maximum in EXP24SX/EXP24S	1536 drives 2764 TB w/ 1.8 TB disk	3072 drives 5529 TB w/ 1.8 TB disk
Performance*		
AIX rPerf	4.02 GHz (8): 674.5(32),	4.02 GHz (8): 1,349.0(64) ^o
GHz (cores/socket): perf (# cores)	4.19 GHz (10): 856.0(40),	4.19 GHz (10): 1,711.9(80) ^o
IBM i CPW	4.02 GHz (8): 359,000(32),	4.02 GHz (8): 711,000(64) ^o
GHz (cores/socket): perf (# cores)	4.19 GHz (10): 460,000(40),	4.19 GHz (10): 911,000(80) ^o

IBM Power Systems
Power E880C

(3-node option also available, but not shown to save space)

Product Line	IBM Power E880C (1 node)	IBM Power E880C (2 node)	IBM Power E880C (4 node)
Machine type	9080-MHE	9080-MHE	9080-MHE
System packaging	19" rack drawer (7U) One 5U system node & one 2U system control unit	19" rack drawer (12U) Two 5U system nodes & one 2U system control unit	19" rack drawer (22U) Four 5U system nodes & one 2U system control unit
Microprocessor type	64-bit POWER8	64-bit POWER8	64-bit POWER8
# of processor sockets per server	4	8 (4 per system node)	16 (4 per system node)
Processor options GHz (cores/socket) # of cores	4.35 GHz (8) 32 4.19 GHz (10) 40 4.02 GHz (12) 48	4.35 GHz (8) 64 4.19 GHz (10) 80 4.02 GHz (12) 96	4.35 GHz (8) 128 4.19 GHz (10) 160 4.02 GHz (12) 192
Minimum number cores active	8	8	8
Energy Scale	Y	Y	Y
Level 2 (L2) cache per core	512 KB	512 KB	512 KB
Level 3 (L3) cache per core	8 MB	8 MB	8 MB
Level 4 (L4) cache per socket	Up to 128 MB	Up to 128 MB	Up to 128 MB
System memory: min / max / (min % active) 1600 MHz DDR3 or DDR4	256 GB / 8 TB / (50%)	512 GB / 16 TB / (50%)	1 TB / 32 TB / (50%)
Active Memory Expansion	Optional	Optional	Optional
Reliability, availability, serviceability			
Chipkill memory	Y	Y	Y
Service processor and clock	Redundant with failover	Redundant with failover	Redundant with failover
Hot-swappable disks	N/A	N/A	N/A
Dynamic Processor Deallocation	Y	Y	Y
Processor Instruction Retry	Y	Y	Y
Alternate Processor Recovery	Y	Y	Y
Hot-plug PCIe slots	Y	Y	Y
Blind-swap PCIe slots in system unit	Y	Y	Y
Blind-swap PCIe slots in PCIe I/O drawer	Y	Y	Y
Active Memory Mirroring	Y	Y	Y
Redundant hot-plug power	Y	Y	Y
Redundant hot-plug cooling	Y	Y	Y
Dual VIOS	Optional	Optional	Optional
Cloud Mgmt and Deployment			
IBM Cloud PowerVC Manager	Included (separately priced)	Included (separately priced)	Included (separately priced)
HMC Apps as a Server	No charge when available	No charge when available	No charge when available
Cloud Starter Pack	12 months access	12 months access	12 months access
Convert Power server resources to cloud	Yes	Yes	Yes
IBM API Connect and WebSphere Connect	Included	Included	Included
Open source cloud automation and configuration tooling for AIX	Included	Included	Included
Power-to-Cloud Rewards	20,000 points	20,000 points	20,000 points
Capacity and expandability			
Capacity on Demand (CoD) functions	Y ^{A,B}	Y ^{A,B}	Y ^{A,B}
Power Enterprise Processor Pools	Optional	Optional	Optional
Power Integrated Facility for Linux	Optional	Optional	Optional
PowerVM Enterprise Edition	Standard	Standard	Standard
Max logical partitions/micro-partitions	960 (20 per core max)	1000	1000
Max system node PCIe Gen3 x16 slots	8	16 (8 per enclosure)	32 (8 per enclosure)
Max PCIe Gen3 I/O Drawers	4	8 (4 per node)	16 (4 per node)
Max PCIe Gen3 slots (all PCIe I/O drawers)	48	96	192
System Control Unit: media bay	1 optional DVD	1 optional DVD	1 optional DVD
Max disk storage in system unit	N/A	N/A	N/A
Max EXP24S/EXP24SX/EXP12SX	64	128	168
Maximum in EXP12SX	768 drives 5929 TB w/ 7.72TB	1536 drives 11858 TB w 7.72TB	2016 drives 15563 TB w/ 7.72TB
Maximum in EXP24SX/EXP24S	1536 drives 2764 TB w/ 1.8TB	3072 drives 5529 TB w/ 1.8TB	4032 drives 7257 TB with 1.8TB
Performance*			
rPerf	U		
GHz (cores/socket): perf (# cores)	4.35 GHz (8): 716.3(32), 4.19 GHz (10): 856.0 (40) 4.0 GHz (12): 976.4 (48)	4.35 GHz (8): 1,432.5(64) ° 4.19 GHz (10): 1,711.9 (80) ° 4.0 GHz (12): 1952.9(96)	4.35 GHz (8): 2,865 (128) ° 4.19 GHz (10): 3,424.0 (160) ° 4.0 GHz (12): 3905.8 (192)
IBM i CPW	4.35 GHz (8): 381,000(32) 4.19 GHz (10): 460,000 (40) 4.02 GHz (12): 518,000(48)	4.35 GHz (8): 755,000(64) ° 4.19 GHz (10): 911,000 (80) 4.02 GHz (12): 1,034,000(96)	4.35 GHz (8): 1,523,000 (128) ° 4.19 GHz (10): 1,813,000 (160) 4.02 GHz (12): 2,069,000 (192)

Note: A 3-node column is not shown above to save space and allow a larger font to be used. 4.35GHz 3-node 96-core rPerf = 2,148.8 ° and CPW = 1,144,000 ° 4.19GHz 3-node 120-core rPerf = 2,568.0 ° and CPW = 1,362,000 ° 4.02GHz 3-node 144-core rPerf = 2,929.3 ° and CPW = 1,551,000 °

Power E880 (withdrawal from marketing announced Feb 2017, effective 17 July^B see E880C)

(3-node option also available, but not shown to save space)

Product Line	IBM Power E880 (1 node)	IBM Power E880 (2 node)	IBM Power E880 (4 node)
Machine type	9119-MHE	9119-MHE	9119-MHE
System packaging	19" rack drawer (7U) One 5U system node & one 2U system control unit	19" rack drawer (12U) Two 5U system nodes & one 2U system control unit	19" rack drawer (22U) Four 5U system nodes & one 2U system control unit
Microprocessor type	64-bit POWER8	64-bit POWER8	64-bit POWER8
# of processor sockets per server	4	8 (4 per system node)	16 (4 per system node)
Processor options	4.35 GHz (8) 32 4.19 GHz (10) 40 4.02 GHz (12) 48	4.35 GHz (8) 64 4.19 GHz (10) 80 4.02 GHz (12) 96	4.35 GHz (8) 128 4.19 GHz (10) 160 4.02 GHz (12) 192
Minimum number cores active	8	8	8
Energy Scale	Y	Y	Y
Level 2 (L2) cache per core	512 KB	512 KB	512 KB
Level 3 (L3) cache per core	8 MB	8 MB	8 MB
Level 4 (L4) cache per socket	Up to 128 MB	Up to 128 MB	Up to 128 MB
System memory: min / max / (min % active) 1600 MHz DDR3	256 GB / 8 TB / (50%)	512 GB / 16 TB / (50%)	1 TB / 32 TB / (50%)
Active Memory Expansion	Optional	Optional	Optional
Reliability, availability, serviceability			
Chipkill memory	Y	Y	Y
Service processor and clock	Redundant with failover	Redundant with failover	Redundant with failover
Hot-swappable disks	N/A	N/A	N/A
Dynamic Processor Deallocation	Y	Y	Y
Processor Instruction Retry	Y	Y	Y
Alternate Processor Recovery	Y	Y	Y
Hot-plug PCIe slots	Y	Y	Y
Blind-swap PCIe slots in system unit	Y	Y	Y
Blind-swap PCIe slots in PCIe I/O drawer	Y	Y	Y
Active Memory Mirroring	Y	Y	Y
Redundant hot-plug power	Y	Y	Y
Redundant hot-plug cooling	Y	Y	Y
Dual VIOS	Optional	Optional	Optional
Capacity and expandability			
Capacity on Demand (CoD) functions	Y ^{A,B}	Y ^{A,B}	Y ^{A,B}
Power Enterprise Processor Pools	Optional	Optional	Optional
Power Integrated Facility for Linux	Optional	Optional	Optional
PowerVM Enterprise Edition	Standard	Standard	Standard
Max logical partitions/micro-partitions	960 (20 per core max)	1000	1000
Max system node PCIe Gen3 x16 slots	8	16 (8 per enclosure)	32 (8 per enclosure)
Max PCIe Gen3 I/O Drawers	4	8 (4 per node)	16 (4 per node)
Max PCIe Gen3 slots (all PCIe I/O drawers)	48	96	192
System Control Unit: media bay	1 optional DVD	1 optional DVD	1 optional DVD
Max disk storage in system unit	N/A	N/A	N/A
Maximum EXP24S/EXP24SX/EXP12SX storage enclosures	64	128	168
Maximum in EXP12SX	768 drives 5929 TB with 7.72TB disk	1536 drives 11858 TB with 7.72TB disk	2016 drives 15563 TB with 7.72TB disk
Maximum in EXP24SX/EXP24S	1536 drives 2764 TB w/ 1.8 TB disk	3072 drives 5529 TB w/ 1.8 TB disk	4032 drives 7257 TB with 1.8 TB disk
Performance*			
rPerf	4.35 GHz (8): 716.3(32), 4.19 GHz (10): 856.0 (40) 4.0 GHz (12): 976.4 (48)	4.35 GHz (8): 1,432.5(64) ° 4.19 GHz (10): 1,711.9 (80) ° 4.0 GHz (12): 1,952.9(96)	4.35 GHz (8): 2,865 (128) ° 4.19 GHz (10): 3,424.0 (160) ° 4.0 GHz (12): 3,905.8 (192)
IBM i CPW	4.35 GHz (8): 381,000(32) 4.19 GHz (10): 460,000 (40) 4.02 GHz (12): 518,000(48)	4.35 GHz (8): 755,000(64) ° 4.19 GHz (10): 911,000 (80) 4.02 GHz (12): 1,034,000(96)	4.35 GHz (8): 1,523,000 (128) ° 4.19 GHz (10): 1,813,000 (160) 4.02 GHz (12): 2,069,000 (192)

Note: A 3-node column is not shown above to save space and allow a larger font to be used. 4.35GHz 3-node 96-core rPerf = 2,148.8 ° and CPW = 1,144,000 ° 4.19GHz 3-node 120-core rPerf = 2,568.0 ° and CPW = 1,362,000 ° 4.02GHz 3-node 144-core rPerf = 2,929.3 ° and CPW = 1,551,000 °

System Unit Details (Power Systems S LC Class Servers)

System Unit Details	Power S812LC	Power S822LC
POWER8 SCM sockets	1	2
Number of SCMs	1	2
Max memory DIMM slots	32	32 (8 riser slots)
Max sustained memory bandwidth to L4 cache from SCM	115 GB/sec	115 GB/sec per socket, 230 GB/sec per system
Max peak memory bandwidth to DIMMs from L4 cache	170 GB/sec	170 GB/sec per socket, 340 GB/sec per system
Integrated ports		
System/serial (RJ45)	0	0
USB-3	3 (1 front & 2 rear)	2 (1 front * & 1 rear)
VGA	1	1
RJ45 for BMC and IMPI	1 (10/100 MbE)	1 (1GbE)
DB9 for BMC and IMPI	1	1
USB-1	1 Not enabled for client	1 internal Not enabled for client
Ethernet for general use	N/A	N/A
HMC ports	N/A (BMC used)	N/A (BMC used)
PCIe Ethernet adapter	optional	1 required ^a
SATA bays in system unit		
2.5-inch (SFF) only	N/A	2 SFF-4
3.5-inch (LFF) or SFF	14	0
Media bays		
DVD-RAM slimline	N/A	N/A
HH for tape	N/A	N/A
SATA storage controllers for disk/SSD		
Base backplane	Y, mezz card	Y, integrated
Split backplane	Optional **	N/A
RAID adapter	Optional ***	N/A
Hybrid RAID function	Optional ***	N/A
Optional EXP24S ports	N/A	N/A
PCIe Gen3 adapter slots		
PCIe x8	4	5
PCIe x16	3	2
Max PCIe bus speed (GHz)	8.0 (Gen3)	8.0 (Gen3)
Max I/O bandwidth*	64 GB/sec	128 GB/sec
Service indicator LEDs	Y	Y

* front USB-3 port run at USB-2 bandwidth

** Split is 2 bays in rear tray run by integrated mezzanine card and 12 bays in front run by PCIe adapter

*** RAID and hybrid RAID on the 12 bays in the front run by a PCIe adapter

System Unit Details (Power Systems S Class Servers)

System Unit Details	Power S812 1-core	Power S812 4-core	Power S812L	Power S822 Power S822L
POWER8 DCM sockets	1	1	1	2
Number of DCMs	1	1	1	1 or 2 for S822 2 for S822L
Max memory DIMM card slots	4 supported	8	8	16 (with 2 DCM)
Max sustained memory bandwidth to L4 cache from DCM	96 GB/sec	192 GB/sec	192 GB/sec	384 GB/sec
Max peak memory bandwidth to DIMMs from L4 cache	210 GB/sec	410 GB/sec	410 GB/sec	820 GB/sec
Integrated ports				
System/serial (RJ45)	1	1	1	1
USB-2 ports ^g	2	2	2	2
USB-3 ports	4 (2 front & 2 rear)	4 (2 front & 2 rear)	4 (2 front & 2 rear)	2 (2 front & 0 rear)
HMC ports (RJ45)	2	2	2	2
Ethernet adapter ports ^a	4x 1 Gb	4x 1 Gb or 2x 10/1 Gb	4x 1 Gb or 2x 10/1 Gb	4x 1 Gb or 2x 10/1 Gb
SAS bays in system unit				
2.5-inch (disk/SSD)	8 SFF-3	12 or 8 SFF-3	12 or 8 SFF-3	12 or 8 SFF-3
1.8-inch (SSD)	0	0	0	0 or 6
Media bays				
DVD-RAM slimline	1	1	1	1
HH for tape	N/A	N/A	N/A	N/A
Integrated SAS storage controllers for disk/SSD/DVD	Y	Y	Y	Y
Base backplane	1 (zero write cache)	1 (zero write cache)	1 (zero write cache)	1 (zero write cache)
Split backplane	2 (zero write cache)	2 (zero write cache)	2 (zero write cache)	2 (zero write cache)
Expanded function backplane ^{b, c}	Dual IOA (7.2 GB write cache) ^{b, c}	Dual IOA (7.2 GB write cache) ^{b, c}	Dual IOA (7.2 GB write cache) ^{b, c}	Dual IOA (7.2 GB write cache) ^{b, c}
Easy Tier function	N/A	Y with expanded function backplane	Y with expanded function backplane	Y with expanded function backplane
Optional EXP24SX or EXP12SX ports	N/A	Y with expanded function backplane	Y with expanded function backplane	Y with expanded function backplane
PCIe Gen3 adapter slots	6	6	6	9 (w/ 2 DCM)
PCIe x8	4	4	4	5
PCIe x16	2	2	2	4
Max PCIe bus speed (GHz)	8.0 (Gen3)	8.0 (Gen3)	8.0 (Gen3)	8.0 (Gen3)
Max I/O bandwidth	96 GB/sec	96 GB/sec	96 GB/sec	96 GB/sec per DCM
Service indicator LEDs	Y	Y	Y	Y

Storage backplane notes: Integrated SAS controllers are based on latest IBM patented SAS RAID adapter technology. All backplane options offer RAID 0, 1, 5, 6, 10 capabilities plus hot spare capability. Write cache is mirrored for protection and physically is two 1.8 GB DRAM caches offering up to 7.2 GB effective capacity with compression. One optional EXP24S storage drawer attachment is to two SAS ports on rear of server which is available with the expanded function backplane. The EXP24S is external to the system unit taking 2U rack space and attached via SAS cables and provides 24 SSF-2 SAS bays for disk or for SSD.

System Unit Details (Power Systems S Class Servers)

System Unit Details	Power S814	Power S824	Power S824L
POWER8 DCM sockets	1	2	2
Number of DCMs	1	1 or 2	1 ^P or 2
Max memory DIMM card slots	4-core: 4 usable 6/8-core: 8	16 (with 2 DCM)	16
Max sustained memory bandwidth to L4 cache from DCM	4-core: 96 GB/sec 6/8-core: 192 GB/sec	384 GB/sec (with 2 DCM)	384GB/sec
Max peak memory bandwidth to DIMMs from L4 cache	4-core: 205 GB/sec 6/8-core: 410 GB/sec	820 GB/sec (with 2 DCM)	820 GB/sec
Integrated ports			
System/serial (RJ45)	1	1	1
USB-2 ports ^g	2	2	2
USB-3 ports	4 (2 front & 2 rear)	4 (2 front & 2 rear)	4 (2 front & 2 rear)
HMC ports (RJ45)	2	2	2
Ethernet adapter ports ^a	4x 1 Gb or 2x 10/1 Gb	4x 1 Gb or 2x 10/1 Gb	2 1 Gb
SAS bays in system unit			
2.5-inch (disk/SSD)	4-core: 10 usable 6/8-core: 12 or 18 SFF-3	12 or 18 SFF-3	12 SFF-3 or 18 SFF-3 ^P
1.8-inch (SSD)	0	0 or 8	0 or 8 ^P
Media bays			
DVD-RAM slimline	1	1	1
HH for tape	N/A	N/A	N/A
Integrated SAS storage controllers for disk/SSD/DVD			
Base backplane	1 (zero write cache)	1 (zero write cache)	1 (zero write cache)
Split backplane	2 (zero write cache)	2 (zero write cache)	2 (zero write cache) ^Y
Expanded function backplane ^{b, c}	Dual IOA (7.2 GB write cache) ^{b, c}	Dual IOA (7.2 GB write cache) ^{b, c}	Dual IOA (7.2 GB write cache) ^{b, c, P}
Easy Tier function	Y with expanded function backplane	Y with expanded function backplane	Y with expanded function backplane ^P
Optional EXP24S ports	Y with expanded function backplane	Y with expanded function backplane	Y with expanded function backplane ^P
PCIe Gen3 adapter slots	7	11 (w/ 2 DCM)	11
PCIe x8	5	7	7
PCIe x16	2	4	4
Max PCIe bus speed (GHz)	8.0 (Gen3)	8.0 (Gen3)	8.0(Gen3)
Max I/O bandwidth	96 GB/sec	96 GB/sec per DCM	192 GB/sec
Service indicator LEDs	Y	Y	Y

Storage backplane notes: Integrated SAS controllers are based on latest IBM patented SAS RAID adapter technology. All backplane options offer RAID 0, 1, 5, 6, 10 capabilities plus hot spare capability. Write cache is mirrored for protection and physically is two 1.8 GB DRAM caches offering up to 7.2 GB effective capacity with compression. One optional EXP24S storage drawer attachment is to two SAS ports on rear of server which is available with the expanded function backplane. The EXP24S is external to the system unit taking 2U rack space and attached via SAS cables and provides 24 SSF-2 SAS bays for disk or for SSD.

System Unit Details (Power Enterprise Servers)

Power E850C / E850

System Unit Details	With 2 processor modules	With 3 processor modules	With 4 processor modules
POWER8 sockets	4 (2 filled)	4 (3 filled)	4 (4 filled)
Number of processor modules	2	3	4
Memory DIMM slots	16	24	32
Max sustained memory bandwidth to L4 cache from DCM	384 GB/sec	576 GB/sec	768 GB/sec
Max peak memory bandwidth to DIMMs from L4 cache	820 GB/sec	1230 GB/sec	1640 GB/sec
Integrated ports			
System/serial (RJ45)	1	1	1
USB-2 ports ⁹	2	2	2
USB-3 ports	4 (2 front & 2 rear)	4 (2 front & 2 rear)	4 (2 front & 2 rear)
HMC ports (RJ45)	2	2	2
Ethernet adapter ports ^a	2-4 ports, 1Gb and/or 10Gb depending on PCIe adapter selected	2-4 ports, 1Gb and/or 10Gb depending on PCIe adapter selected	2-4 ports, 1Gb and/or 10Gb depending on PCIe adapter selected
SAS bays in system unit			
2.5-inch (disk/SSD)	8 SFF-3	8 SFF-3	8 SFF-3
1.8-inch (SSD)	4	4	4
Media bays			
DVD-RAM slimline	1	1	1
HH for tape	N/A	N/A	N/A
Integrated SAS storage controllers for disk/SSD/DVD	Y	Y	Y
Dual non-split backplane	Dual IOA (zero write cache)	Dual IOA (zero write cache)	Dual IOA (zero write cache)
Split backplane	2 (zero write cache)	2 (zero write cache)	2 (zero write cache)
Write cache backplane	Dual IOA (7.2 GB write cache)	Dual IOA (7.2 GB write cache)	Dual IOA (7.2 GB write cache)
Easy Tier function	Y with any backplane	Y with any backplane	Y with any backplane
Optional EXP24S ports	N/A	N/A	N/A
PCIe Gen3 adapter slots	7	9	11
PCIe x8	3	3	3
PCIe x16	4	6	8
Max PCIe bus speed (GHz)	8.0 (Gen3)	8.0 (Gen3)	8.0 (Gen3)
Max I/O bandwidth	192 GB/sec	256 GB/sec	320 GB/sec
Service indicator LEDs	Y	Y	Y

Storage backplane notes: Integrated SAS controllers are based on latest IBM patented SAS RAID adapter technology. All backplane options offer RAID 0, 1, 5, 6, 10 capabilities plus hot spare capability plus Easy Tier function assuming enough drives are physically installed to do so. Write cache is mirrored for protection and physically is two 1.8 GB DRAM caches offering up to 7.2 GB effective capacity with compression.

System Node and System Control Unit Details (Power Enterprise Servers)**Power E870C / E870 / E880C / E880**

System Unit Details	Power E870C system node	Power E870 system node	Power E880C system node	Power E880 system node	System control unit (one per system)
POWER8 SCM sockets	4	4	4	4	N/A
Number of SCMs	4	4	4	4	N/A
Memory CDIMM slots	32	32	32	32	N/A
Max sustained memory bandwidth to L4 cache from SCM	230 GB/sec per socket, 920 G/sec per node	230 GB/sec per socket, 920 G/sec per node	230 GB/sec per socket, 920 G/sec per node	230 GB/sec per socket, 920 G/sec per node	N/A
Max peak memory bandwidth to DIMMs from L4 cache	410 GB/sec per socket, 1640 GB/sec per socket	410 GB/sec per socket, 1640 GB/sec per socket	410 GB/sec per socket, 1640 GB/sec per socket	410 GB/sec per socket, 1640 GB/sec per socket	N/A
Integrated ports					
System/serial (RJ45)	N/A	N/A	N/A	N/A	N/A
USB ports	N/A	N/A	N/A	N/A	N/A
HMC ports (RJ45)	0	0	0	0	4
Ethernet adapter ports ^a	N/A	N/A	N/A	N/A	N/A
SAS bays in unit					
2.5-inch (disk/SSD)	N/A	N/A	N/A	N/A	N/A
1.8-inch (SSD)	N/A	N/A	N/A	N/A	N/A
Media bays					
DVD-RAM slimline	0	0	0	0	1
Integrated SAS storage controllers for disk/SSD/DVD	N/A	N/A	N/A	N/A	N/A
PCIe Gen3 adapter slots	8	8	8	8	N/A
PCIe x8	0	0	0	0	N/A
PCIe x16	8	8	8	8	N/A
Max PCIe bus speed (GHz)	8.0 (Gen3)	8.0 (Gen3)	8.0 (Gen3)	8.0 (Gen3)	N/A
Max I/O bandwidth (peak)	256 GB/sec	256 GB/sec	256 GB/sec	256 GB/sec	N/A
Service indicator LEDs	Y	Y	Y	Y	Y
Operator panel	N/A	N/A	N/A	N/A	1

Server PCIe I/O Drawers

Drawer	Server Attachment	PCIe Slots per Drawer	SAS Bays per Drawer	Available to order	Drawer Footprint
PCIe Gen3 I/O Drawer (#EMX0 / ELMX)	via x16 PCIe slot	6 or 12	0	Y	19" rack 4U

Server I/O Drawer Attachment

Server Drawer	Power S812L	Power S812 1-core	Power S812 4-core	Power S822 Power S822L	Power S814 4-core	Power S814 6/8-core	Power S824	Power S824L
PCIe	Max ½	n/a	n/a	Max 1	n/a	Max 1	Max 2	Max 2 ^p

Server Drawer	Power E850C	Power E850	Power E870C or E870	Power E880C or E880
PCIe	Max 4	Max 4	Max 8	Max 16

PCIe Gen3 I/O Expansion Drawer notes

- PCIe Gen3 I/O drawer is not supported on the S812, S812LC or S822LC models.
- Each I/O drawer holds one or two 6-slot fan-out modules. A drawer with just one fan-out module is labeled “½” in this document. Each fan-out module is attached to a x16 PCIe slot in the Scale-out system unit or in the Enterprise system node or CEC.
- The attachment card in a 4U POWER8 server or in a 5U E870 or E880 Enterprise system node uses one PCIe slot. The attachment card in a 2U Scale-out server is a double-wide card using two PCIe slots.
- Each fan-out module provides 6 PCIe Gen3 slots. Two of the six slots are x16 and four are x8.
- Up to four drawers on an E850 and up to four drawers per each system node of an E870/E880 system
- PCIe Gen3 I/O drawers can not be shared between two servers
- For good cable management practices, a maximum of 4 PCIe Gen3 I/O drawers per 7014-T42/T00 rack is generally recommended for configurations using a large number of 4-port PCIe adapters with cables attached to all the ports. If the rack has an 8-inch rear extender making it deeper and able to manage more cables, then a maximum of 6 PCIe Gen3 I/O drawers is recommended.
- Peak I/O bandwidth per fan-out module is 32 GB/sec.

For additional connectivity information, please reference the IBM Sales Manual for more information on I/O features and adapters.

Server I/O SAS Enclosure Units

Drawer	Server Attachment	PCIe Slots per Drawer	SAS Bays per Drawer	Available to order	Drawer Footprint
EXP12SX (#ESLL / #ELL)	Via SAS	0	12 LFF-1 SAS	Y	19" rack 2U
EXP24SX (#ESLS / #ELLS)	Via SAS	0	24 SFF-2 SAS	Y	19" rack 2U
EXP24S (#5887 / #EL1S)	via SAS	0	24 SFF-2 SAS	Y	19" rack 2U

Server I/O Drawer Attachment

Server Drawer	Power S812L	Power S812	Power S812	Power S822	Power S814	Power S814	Power S824	Power S824L
	-	1-core	4-core	Power S822L	4-core	6/8-core		
EXP12SX	Max 28	n/a	Max 3	Max 28	n/a	Max 28	Max 28	Max 28 ^P
EXP24SX	Max 28	n/a	Max 3	Max 28	n/a	Max 28	Max 28	Max 28 ^P
EXP24S	Max 28	n/a	n/a	Max 28	n/a	Max 28	Max 28	Max 28 ^P

Server Drawer	Power E850C	Power E850	Power E870C or E870	Power E880C or E880
EXP12SX	Max 64	Max 128	Max 128	Max 168
EXP24SX	Max 64	Max 128	Max 128	Max 168
EXP24S	Max 64	Max 64	Max 128	Max 168

EXP12SX/EXP24SX/EXP24S storage enclosure notes:

- The maximum drawer attachment is shown above per type of drawer. But it is also a “combined” server maximum. For example, if the maximum shown above is for 14 drawers, it would be combined total of EXP12SX, EXP24SX and EXP24S which would be 14. It would not be 14+14+14 for a combined total of 42.
- The EXP12SX and EXP24SX are designed for 12Gb throughput. Currently no 12Gb SAS adapters are announced. Thus like the EXP24S a 6Gb interface is provided.
- The EXP12SX and EXP24SX are attached to PCIe3 SAS adapters or to integrated POWER8 SAS controllers. They are not attached to older PCIe SAS adapters.
- The EXP12SX supports large capacity 3.5-inch (LFF) disk drives which are 7200 rpm. 4k byte sector drives are supported. Big data applications are its primary usage.
- The EXP12SX is not supported by IBM i.
- The EXP24SX supports 2.5-inch (SFF) SSD and 10k/15k rpm disk drives. 4k and 5x byte sector drives are supported.
- A Power S812L, S814, S822L, S824, S824L Scale-out server has a maximum of 14 storage enclosures if only a system unit is used. The maximum of 28 requires one or more PCIe Gen3 I/O Drawer to be present.
- A Power E850 has a maximum of 16 storage enclosures if only a system unit is used. To support the maximum of 64, three or four PCIe Gen3 drawers are needed.
- A single system node Power E870/E880 with 4 PCIe drawers has a maximum of 64 storage enclosures. A two-node Power E870/E880 with 8 PCIe drawers has a max of 128 storage enclosures. A three or four node Power E880 has a max of 168 storage enclosures. PCIe Gen3 drawers are required to attain this maximum.
- These storage enclosures are not supported on the S812LC or S822LC models.
- A maximum of 16 storage enclosures can be attached to one PCIe Gen3 I/O drawer due to cable management considerations

For additional connectivity information, please reference the IBM Sales Manual for more information on I/O features and adapters.

Physical Planning Characteristics

Note: More comprehensive information may be found in the IBM Site and Hardware Planning document at <http://www.ibm.com/support/knowledgecenter/POWER8/p8hdx/POWER8welcome.htm> . Plus, additional summary information can be found in the IBM Sales Manual for each server at [ibm.com/common/ssi](http://www.ibm.com/common/ssi) .

Server	Power S812LC	Power S822LC 8335-GTA	Power S822LC 8335-GCA
Packaging	19" rack drawer (2U)	19" rack drawer (2U)	19" rack drawer (2U)
Power supplies used	Two 1000 or 1200W N + 1 standard	Two 1300W N+1 standard	Two 1300W N+1 standard
Voltage (AC) single phase	100 - 120 or 200 - 240	200 - 240	200 - 240
Maximum altitude			
Feet	10000	10000	10000
Meters	3048	3048	3048

Server	Power S812 Power S812L	Power S822 Power S822L	Power S814 (rack)	Power S814 (tower)	Power S824 Power S824L
Packaging	19" rack drawer (2U)	19" rack drawer (2U)	19" rack drawer (4U)	Tower	19" rack drawer (4U)
Power supplies used	Two 900W N + 1 standard	Two 1400W N+1 standard	Two 1400W N+1 standard	Two 900W N+1 standard	Four 900W N+1 standard
Voltage (AC) single phase	100 - 120 or 200 - 240	200 - 240	100 - 120 or 200 - 240	100 - 120 or 200 - 240	100 - 120 or 200 - 240
Maximum altitude					
Feet	10000	10000	10000	10000	10000
Meters	3048	3048	3048	3048	3048

Server	Power E850C	Power E850	Power E870C / E870 / E880C / E880 System node	Power E870C / E870 / E880C / E880 System control unit
Packaging	19" rack drawer 4U	19" rack drawer 4U	19" rack drawer 5U per node	19" rack drawer (one per 870/880) 2U
Power supplies used	Four 2000W N + 1 standard	Four 1400W N + 1 standard	Four 1720W per node N + 1 standard	Zero – redundant power input from system node(s)
Voltage (AC) single phase	200 - 240	200 - 240	200 - 240	n/a
Maximum altitude				
Feet	10000	10000	10000	10000
Meters	3050	3050	3048	3048

Note: As an alternative to AC power supplies, HVDC power supplies are available for the S812L, S822, S822L, S814, S824, S824L, E850, E870 and E880 and for the PCIe Gen3 I/O drawer. HVDC power supplies are not announced for the HMC, EXP24S, EXP12SX, EXP24SX I/O Drawer.

Racks	7014-S25 or #0555	7014-T00 or #0551	7014-T42 or #0553	7014-B42	7965-94Y Slim Rack
	25U	36U	42U	42U	42U
Height					
Inches	49.0	71.0 – 75.8	79.3	79.3	78.8
Millimeters	1344	1804 – 1926	2015	2015	2002
Width (can vary depending on use of side panels)					
Inches	23.8	24.5 – 25.4	24.5 - 25.4	24.5 - 25.4	23.6
Millimeters	605	623 – 644	623 – 644	623 - 644	600
Depth (can vary depending on door options selected)					
Inches	39.4	41.0 – 45.2	41.0 - 45.2	41.0 - 55.5	43.1 – 48.2
Millimeters	1001	1042 – 1098	1043 – 1098	1042 - 1409	1095 - 1224

Power E870 and E880 are supported by IBM Manufacturing only in the 7014-T42 or #0553.

Warranty¹ / Installation

Warranty Service Levels	Power S812LC Power S822LC	Power S812 Power S812L	Power S822 Power S822L	Power S814	Power S824 Power S824L
24x7 with two hour service objective ²	Optional	Optional	Optional	Optional	Optional
24x7 with four hour service objective	Optional	Optional	Optional	Optional	Optional
9x5 with four hour service objective	Optional	Optional	Optional	Optional	Optional
9x5 next-business-day	Standard ⁶	Standard ³	Standard ³	Standard ³	Standard ³
Warranty Period	3 years	3 years	3 years	3 years	3 years
Server install⁴	CSU	CSU	CSU	CSU	CSU

Warranty Service Levels	Power E850C	Power E850	Power E870C	Power E870	Power E880C	Power E880
24x7 with two hour service objective ²	Optional	Optional	Optional	Optional	Optional	Optional
24x7 with four hour service objective	Included*	Included*	Standard	Standard	Standard	Standard
9x5 with four hour service objective	-	-	-	-	-	-
9x5 next-business-day	Standard	Standard	-	-	-	-
Warranty Services Period	3 / 1 years ⁵	3 / 1 years ⁵	1 year	1 year	1 year	1 year
Server installation⁴	CSU	CSU	IBI	IBI	IBI	IBI

1. These warranty terms and conditions are for the United States and may be different in other countries. Consult your local IBM representative or IBM Business Partner for country-specific information.

2. Available in selected cities.

3. Mandatory Customer Replaceable Unit (CRU) or Limited On-site service depending on the feature code. With an upgrade to a higher support service level, the mandatory CRU features become optional CRU.

4. CSU = Customer Set Up, IBI = Installation by IBM For server hardware only. Note for IBI servers, server feature codes such as an EXP24S I/O drawer or PCIe Gen3 I/O drawer or PCIe adapter or disk drive are installed by the IBM service representative as part of the normal warranty/maintenance coverage. Optionally a client may choose to install CSU features without an IBM service representative.

5. System is provided with a one year standard warranty 9x5 NBD. For your convenience, IBM has provided an upgrade to 24x7 coverage PLUS two additional years of extended warranty services (varies by country).

6. Mandatory Customer Replaceable Unit (CRU). With an upgrade to a higher support service level, mandatory CRU becomes optional CRU.

Power S LC Class Servers Software Support

Power Systems Software	Power S812LC	Power S822LC 8335-GTA	Power S822LC 8335-GCA
Software Tier	Small	Small	Small
PowerVM™			
PowerVM Linux Edition	N/A	N/A	N/A
PowerVM Standard and Enterprise Editions	N/A	N/A	N/A
PowerKVM 3.1	Supported	N/A	Supported
AIX			
AIX	N/A	N/A	N/A
IBM i			
IBM i	N/A	N/A	N/A
Linux			
Red Hat Enterprise Linux 6.6 and 7.1 (BE)	Supported	Supported	Supported
Red Hat Enterprise Linux 7.2 (BE and LE)	Supported	Supported	Supported
SUSE Linux Enterprise Server 11 (BE)	Supported	Supported	Supported
SUSE Linux Enterprise Server 12 * (LE)	Supported	Supported	Supported
Ubuntu 14.04 (LE)	Supported	Supported	Supported
PowerHA™			
PowerHA SystemMirror for AIX Standard and Enterprise Editions	N/A	N/A	N/A
PowerHA SystemMirror for i	N/A	N/A	N/A

* Or later version

Power S Class Servers Software Support

Power Systems Software	Power S812 1-core	Power S812 4-core	Power S812L	Power S822	Power S822L
Software Tier	Small	Small	Small	Small	Small
PowerVM™					
PowerVM Linux Edition	N/A	N/A	Supported	N/A	Supported
PowerVM Standard and Enterprise Editions	N/A	N/A	N/A	Supported	N/A
PowerKVM					
	N/A	N/A	Supported	N/A	Supported
AIX ***					
AIX 6.1 *	N/A	Supported	N/A	Supported	N/A
AIX 7.1 *	N/A	Supported	N/A	Supported	N/A
AIX 7.2 *	N/A	Supported	N/A	Supported	N/A
IBM i					
IBM i Software Tier	P05	N/A	N/A	Small P10 ^{3,5}	N/A
IBM i 7.1 TR8 *	N/A	N/A	N/A	Supported ^s	N/A
IBM i 7.2 *	Supported	N/A	N/A	Supported ^s	N/A
IBM i 7.3 *	Supported	N/A	N/A	Supported ^s	N/A
Linux					
Red Hat Enterprise Linux 6.6 *(BE)	N/A	N/A	Supported	Supported	Supported
Red Hat Enterprise Linux 7.1(LE and BE)	N/A	N/A	Supported	Supported	Supported
RedHat Enterprise Linux 7.2(LE and BE)	N/A	N/A	Supported	N/A	Supported
SUSE Linux Enterprise Server 11 (BE) 12(LE)	N/A	N/A	Supported	Supported	Supported
Ubuntu 14.04 (LE)	N/A	N/A	Supported	N/A	Supported
PowerHA™					
PowerHA SystemMirror for AIX 6.1 ² Standard and Enterprise Editions	Supported	Supported	N/A	Supported	N/A
PowerHA SystemMirror for AIX 7 ² Standard Edition	Supported	Supported	N/A	Supported	N/A
PowerHA SystemMirror for IBM i Version7 Standard and Enterprise Editions	Supported	Supported	N/A	Supported	N/A

* Or later

*** See www.ibm.com/support/docview.wss?uid=ssm1platformaix to determine specific Technology Level and Service Pack requirements

1 – Note that AIX 6.1 and AIX 7.1 Express Edition may be used for partitions of up to 4 cores and 8 GB of memory per core.

2 – PowerHA SystemMirror for AIX 6.1 is supported on AIX 5.3, AIX 6.1 and AIX 7.1. PowerHA SystemMirror for AIX 7 is supported with both AIX 6.1 and AIX 7.1

3 – P05 and P10 require user entitlements and includes 5250 Enterprise Enablement capability. P20 does not have user entitlements and 5250 Enterprise Enablement is ordered as an optional hardware feature code.

4. When no GPU installed

5. There is a maximum of two cores per IBM i partition on a S822 server. Multiple IBM i partitions on a server are supported. IBM i 7.1 TR11 or 7.2 TR3 or or 7.3 or later is required. Also note all I/O is virtualized through VIOS, there is no "native" non-VIOS I/O.

Power S Class Servers Software Support

Power Systems Software	Power S814	Power S824	Power S824L
Software Tier	Small	Small	Small
PowerVM™			N/A
PowerVM Linux Edition	N/A	N/A	Supported ⁴
PowerVM Standard and Enterprise Editions	Supported	Supported	N/A
PowerKVM	N/A	N/A	Supported ⁴
AIX ***			
AIX 6.1 *	Supported	Supported	N/A
AIX 7.1 *	Supported	Supported	N/A
AIX 7.2 *	Supported	Supported	N/A
IBM i			
IBM i Software Tier	Small 4-core: P05 ³ 6/8-core: P10 ³	Small P20 ³	N/A
IBM i 7.1 TR8 *	Supported	Supported	N/A
IBM i 7.2 *	Supported	Supported	N/A
IBM i 7.3 *	Supported	Supported	N/A
Linux			
Red Hat Enterprise Linux 6.6 *(BE)	Supported	Supported	Supported ⁴
Red Hat Enterprise Linux 7.1(LE and BE)	Supported	Supported	Supported ⁴
RedHat Enterprise Linux 7.2(LE and BE)	N/A	Supported	N/A
SUSE Linux Enterprise Server 11 (BE) 12(LE)	Supported	Supported	Supported ⁴
Ubuntu 14.04 (LE)	N/A	N/A	Supported,
PowerHA™			
PowerHA SystemMirror for AIX 6.1 ² Standard and Enterprise Editions	Supported	Supported	N/A
PowerHA SystemMirror for AIX 7 ² Standard Edition	Supported	Supported	N/A
PowerHA SystemMirror for IBM i Version7 Standard and Enterprise Editions	Supported	Supported	N/A

* Or later

*** See www.ibm.com/support/docview.wss?uid=ssm1platformaix to determine specific Technology Level and Service Pack requirements

1 – Note that AIX 6.1 and AIX 7.1 Express Edition may be used for partitions of up to 4 cores and 8 GB of memory per core.

2 – PowerHA SystemMirror for AIX 6.1 is supported on AIX 5.3, AIX 6.1 and AIX 7.1. PowerHA SystemMirror for AIX 7 is supported with both AIX 6.1 and AIX 7.1

3 – P05 and P10 require user entitlements and includes 5250 Enterprise Enablement capability. P20 does not have user entitlements and 5250 Enterprise Enablement is ordered as an optional hardware feature code.

4. When no GPU installed

5. There is a maximum of two cores per IBM i partition on a S822 server. Multiple IBM i partitions on a server are supported. IBM i 7.1 TR11 or 7.2 TR3 or 7.3 or later is required. Also note all I/O is virtualized through VIOS, there is no "native" non-VIOS I/O.

Power Enterprise Servers Software Support

Power Systems Software	Power E850C	Power E850	Power E870C	Power E870	Power E880C	Power E880
Software Tier	Small	Small	Medium	Medium	Medium	Medium
PowerVM™						
PowerVM Linux Edition	With Power IFL	With Power IFL	With Power IFL	With Power IFL	With Power IFL	With Power IFL
PowerVM Standard Edition	N/A	Supported	N/A	N/A	N/A	N/A
PowerVM Enterprise Editions	Standard	Supported	Standard	Standard	Standard	Standard
PowerKVM	N/A	N/A	N/A	N/A	N/A	N/A
AIX ***						
AIX 6.1	Supported	Supported	Supported	Supported	Supported	Supported
AIX 7.1	Supported	Supported	Supported	Supported	Supported	Supported
AIX 7.2 *	Supported	Supported	Supported	Supported	Supported	Supported
IBM i						
IBM i Software Tier	N/A	N/A	P30	P30	P30	P30
IBM i 7.1 TR9 *	N/A	N/A	Supported	Supported	Supported	Supported
IBM i 7.2 TR1 *	N/A	N/A	Supported	Supported	Supported	Supported
IBM i 7.3 *	N/A	N/A	Supported	Supported	Supported	Supported
Linux						
Red Hat Enterprise Linux 6.6(BE) 7.1(BE,LE)	Supported	Supported	Supported	Supported	Supported	Supported
SUSE Linux Enterprise Server 11(BE) 12(LE)	Supported	Supported	Supported	Supported	Supported	Supported
Ubuntu 14.04(LE)	Supported	Supported	Supported	Supported	Supported	Supported
PowerHA™						
PowerHA SystemMirror for AIX 6.1 ² Standard and Enterprise Editions	Supported	Supported	Supported	Supported	Supported	Supported
PowerHA SystemMirror for AIX 7 ² Standard Edition	Supported	Supported	Supported	Supported	Supported	Supported
PowerHA SystemMirror for IBM i Version 7 Standard and Enterprise Editions	N/A	N/A	Supported	Supported	Supported	Supported

* Or later

** IBM i 7.1 TR10 and IBM i 7.2 TR2 are required for 4-node or 4 PCIe I/O drawer per node configurations

*** See www.ibm.com/support/docview.wss?uid=ssm1platformaix to determine specific Technology Level and Service Pack requirements.

Performance Notes

The performance information contained herein is current as of the date of this document. All performance benchmark values and estimates are provided “AS IS” and no warranties or guarantees are expressed or implied by IBM. Buyers should consult other sources of information, including system benchmarks, to evaluate the performance of a system they are considering.

rPerf (Relative Performance) is an estimate of commercial processing performance relative to other IBM UNIX® systems. It is derived from an IBM analytical model which uses characteristics from IBM internal workloads, TPC and SPEC benchmarks. The rPerf model is not intended to represent any specific public benchmark results and should not be reasonably used in that way. The model simulates some of the system operations such as CPU, cache and memory. However, the model does not simulate disk or network I/O operations.

rPerf estimates are calculated based on systems with the latest levels of AIX and other pertinent software at the time of system announcement. Actual performance will vary based on application and configuration specifics. The IBM eServer™ pSeries® 640 is the baseline reference system and has a value of 1.0. Although rPerf may be used to approximate relative IBM UNIX commercial processing performance, actual system performance may vary and is dependent upon many factors including system hardware configuration and software design and configuration. Variations in incremental system performance may be observed in commercial workloads due to changes in the underlying system architecture. For additional information about rPerf, contact your local IBM office or an IBM authorized reseller.

Commercial Processing Workload (CPW) is a relative measure of performance of systems running the IBM i operating system. Performance in client environments may vary. The value is based on maximum configurations. For a complete description Please refer to the “IBM Power Systems Performance Capabilities Reference - IBM i operating system” at the following Web site of CPW and the CPW rating for IBM Power Systems:
www.ibm.com/systems/power/software/i/management/performance/resources.html

All performance estimates are provided “AS IS” and no warranties or guarantees are expressed or implied by IBM. Buyers should consult other sources of information including system benchmarks and application sizing guides to evaluate the performance of a system they are considering buying. Actual system performance may vary and is dependent upon many factors including system hardware configuration and software design and configuration. IBM recommends application-oriented testing for performance predictions. Additional information about the performance benchmarks, values and systems tested is available from your IBM marketing representative or IBM Authorized Reseller or access the following on the Web:

SPEC – <http://www.spec.org>

TPC – <http://www.tpc.org>

More information

Contact your IBM sales representative or IBM Business Partner

Access the Power Systems Products and Services page on IBM’s World Wide Web server at

ibm.com/systems/power and then select the appropriate hardware or software option

Product announcement letters and Sales Manual containing more details on hardware and software offerings are available at ibm.com/common/ssi

More detailed benchmark and performance information is available at

ibm.com/systems/p/hardware/benchmarks , ibm.com/systems/p/hardware/system_perf.html and at ibm.com/systems/i/solutions/perfmgmt/resource.html .



© IBM Corporation 2018

IBM Systems
Route 100
Somers, New York 10589

Produced in the United States of America
January 2018
All Rights Reserved

This document was developed for products and/or services offered in the United States. IBM may not offer the products, features or services discussed in this document in other countries. The information may be subject to change without notice. Consult your local IBM business contact for information on the products, features and services available in your area.

All statements regarding IBM future directions and intent are subject to change or withdrawal without notice and represent goals and objectives only. These are identified by SOD.

IBM, the IBM logo, Active Memory, AIX, BladeCenter, EnergyScale, Power, POWER, POWER8, PowerHA, PowerVM, Power Systems and Power Systems Software are trademarks or registered trademarks of International Business Machines Corporation in the United States or other countries or both. A full list of U.S. trademarks owned by IBM may be found at ibm.com/legal/copytrade.shtml.

The Power Architecture and Power.org wordmarks and the Power and Power.org logos and related marks are trademarks and service marks licensed by Power.org.

UNIX is a registered trademark of the Open Group in the United States, other countries or both.

Linux is a registered trademark of Linux Torvalds in the United States, other countries or both.

TPC-C and TPC-H are trademarks of the Transaction Performance Processing Council (TPPC).

SPECint, SPECfp, SPECjbb and SPECweb are trademarks of the Standard Performance Evaluation Corp (SPEC).

InfiniBand, InfiniBand Trade Association and the InfiniBand design marks are trademarks and/or service marks of the InfiniBand Trade Association.

Other company, product and service names may be trademarks or service marks of others.

IBM hardware products are manufactured from new parts or new and used parts. Regardless, our warranty terms apply.

Photographs show engineering and design models. Changes may be incorporated in production models.

Copying or downloading the images contained in this document is expressly prohibited without the written consent of IBM.

This equipment is subject to FCC rules. It will comply with the appropriate FCC rules before final delivery to the buyer.

Information concerning non-IBM products was obtained from the suppliers of these products or other public sources. Questions on the capabilities of the non-IBM products should be addressed with the suppliers.

All performance information was determined in a controlled environment. Actual results may vary. Performance information is provided "AS IS" and no warranties or guarantees are expressed or implied by IBM.

When referring to storage capacity, total TB equals total GB divided by 1000; accessible capacity may be less.

The IBM home page on the Internet can be found at ibm.com.

This brochure provides detailed technical specifications of all IBM POWER8 processor-based Power Systems servers in a tabular, easy-to-scan format for easy comparison between systems. These systems are UNIX (AIX), IBM i and Linux operating system servers. Not all features listed in this document are available on all three operating systems.

THE INFORMATION IN THIS DOCUMENT IS PROVIDED "AS IS" WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT. IBM products are warranted according to the terms and conditions of the agreements under which they are provided.